



REFRIGERATED TRAILER CUSTOMER PICK-UP POLICY

REFRIGERATED TRAILER CUSTOMER PICK-UP POLICY

Thank you for choosing Leer to fulfill your Refrigerated Trailer needs! Please note, we do allow customer pickup, but for your safety the requirements set out below must be strictly followed.

Pick-Up Options Offered:

1. Pick-Up of Refrigerated Trailer (Body + Trailer) with Tow Vehicle
2. Pick-Up of Refrigerated Trailer (Body + Trailer) with Semi-Trailer
3. Pick-Up of Crated Refrigerated Trailer (Body Only) with Trailer

Requirements:

- Please notify Leer at time of order your requested pick-up option
- Sign and return a copy of the Leer Pick-Up Policy, along with a picture of pick-up trailer/vehicle.
- Schedule a pick-up time during standard business hours.

PICK-UP OF REFRIGERATED TRAILER (BODY + TRAILER) WITH TOW VEHICLE

Refrigerated Trailer Specs:

- 5x10 Refrigerated Trailer:
 - Unloaded Vehicle Weight: 2740 LBS
 - Unloaded Hitch (Tongue) Weight: 590 LBS
 - Gross Vehicle Weight Rating (GVWR): 9990 LBS
 - Overall Length: 15' 7"
 - Trailer Coupling Type: 2-5/16" Ball
 - Trailer Wiring Connection: 7-Way RV Blade
 - Trailer Brake Type: Electric – Both Axles
- 4x8 Refrigerated Trailer:
 - Unloaded Vehicle Weight: 2185 LBS
 - Unloaded Hitch (Tongue) Weight: 325 LBS
 - Gross Vehicle Weight Rating (GVWR): 7000 LBS
 - Overall Length: 13' 9"
 - Trailer Coupling Type: 2-5/16" Ball
 - Trailer Wiring Connection: 7-Way RV Blade
 - Trailer Brake Type: Electric – Both Axles

Tow Vehicle Requirements:

- The maximum towing capacity of your towing vehicle should not be exceeded. The towing capacity of your tow vehicle, in terms of maximum Gross Trailer Weight (GTW) and maximum Gross Combined Weight Rating (GCWR) can be found in the tow vehicle's Owner's Manual.



- **WARNING:** Use of a tow vehicle with a towing capacity less than the load rating of the trailer or a hitch with a load rating less than the load rating of the trailer can result in loss of control and may lead to death or serious injury.
- The use of a Class III or Class IV trailer hitch rated for 10,000lbs
- The use of a 2 5/16" hitch ball
- The use of a trailer brake controller and a 7-Way RV Blade harness connector.

Pick-Up Requirements:

- All trailer connections to tow vehicle shall be completed by individual collecting the trailer order.
- All safety checks shall be completed by the individual collecting the trailer order.
- It is strongly recommended that an individual with the appropriate transportation experience be used to pick-up and deliver the product.
- For safety, children under the age of 18 and pets shall not be allowed in or around the facility and loading bays at time of pick-up.
- A Customer Service Representative should be contacted for tow vehicle recommendations.
- A Customer Service Representative must schedule and approve the pick-up time and date.
- Leer Inc. is not responsible for the product once individual collecting the order accepts delivery of product.
- Leer Inc. reserves the right to refuse trailer connections to any tow vehicle.

PICK-UP OF REFRIGERATED TRAILER (BODY + TRAILER) WITH SEMI-TRAILER

Semi-Trailer Requirements:

- Trailered units must be shipped on standard flatbed semi-trailers or standard enclosed semi-trailers – gooseneck/low-boy or step deck trailers that do not reach standard loading dock height are not acceptable.
- Enclosed Box Trailer (Dry Van) Requirements:
 - 93" minimum door and trailer interior width.
 - 108" minimum door and trailer interior height.
 - Wooden floor for securing 2x4 dimensional lumber wheel chocks.
 - E-Track on both side walls of the trailer no taller than 10" off the floor to center of E-Track.
 - Trailers must be equipped with air ride suspension.





REFRIGERATED TRAILER CUSTOMER PICK-UP POLICY

- The carrier is responsible for checking the load for any DOT height regulations when using a flatbed trailer.
- One exception is a self-loading, center track trailer, equipped with a winch, ramps and a hitch ball post. The individual collecting the trailer order will be responsible for loading and securing the refrigerated trailer

Accepted Trailers for Refrigerated Trailer (Body + Trailer):



PICK-UP OF CRATED REFRIGERATED TRAILER (BODY ONLY) WITH TRAILER

Trailer Requirements:

- Minimum Trailer Deck Dimensions by Model:
 - 5x10 Unit: 67" wide x 147" long
 - 4x8 Unit: 55" wide x 120" long
- The trailer must be free of gates or permanently attached ramps on the rear of the trailer.

Pick-Up Requirements:

- The Customer is responsible for securing the unit to the trailer. Leer does not supply mounting hardware.

Accepted Trailers For Crated Refrigerated Trailer Body (in addition to all Trailers noted for (Body+ Trailer, except for specialized center track winch trailer):



Not Accepted For Crated Refrigerated Trailer Body:





**REFRIGERATED TRAILER
CUSTOMER PICK-UP POLICY**

**LEER INC. IS NOT RESPONSIBLE FOR ANY DAMAGE THAT MAY OCCUR DURING THE LOADING
PROCESS ONTO CUSTOMER TRAILER.**

Customer Acknowledgement:	Date:
----------------------------------	--------------

